

# A.B.N. 67 054 007 162 HAZPAK PTY LTD 44 Stephen Rd, Dandenong South Vic. 3175 Australia Postal Address: P.O. Box 4000, Dandenong South Vic. 3164 Australia Tel: (03) 9706 8058 Fax: (03) 9706 7593 Intl. Tel: 61 3 9706 8058 E-mail: hazpak@hazpak.com.au

# PRODUCT INFORMATION

PRODUCT NAME: Small Fibreboard 1L Plastic PRODUCT TYPE: UN Approved Dangerous

**PRODUCT CODE:** GP-LQ8-IP2-1x1L-58 Goods packaging

**DESCRIPTION:** 'Limited Quantity Combination Pack' with fibreboard outer box, fibreboard

stabilising inserts, liner bag, 500 mL HDPE rectangular jar with 58 mm screw closure

and annular gasket and orientation labels for transport of Dangerous Goods.

IATA Compliant.

## **PHOTOGRAPHS**



Packaging System

FALCON TEST ENGINEERS REPORT No: 3280

# **ASSEMBLY & CONFIGURATION OF PACKAGING:**

Fill the inner packaging with substance, place the closure and tightly close using the spanner. Apply self adhesive tape around the closure as a secondary means of security. Place the inner packaging into the outer fibreboard box. Ensure that it is in a stable upright position and that it is seated firmly on the bottom 'X' insert. Place the top 'X' insert over the inner packaging. Seal plastic bag with a "goose-neck tie". Twist slack of bag tightly, fold over so that it forms a neck, and secure with elastic bands. Tuck neck into box. Close and seal the box with 48 mm pressure sensitive self adhesive tape in the same manner that the base of the box has been sealed. Add the required amount of absorbent material if specified. Label the box as required.

(Make sure that the labels or any other markings are not obliterated or obscured in any way). Note: The use of other packaging methods or components may render the approval of this package invalid.

## **MARKINGS & APPROVAL:**

Approval No.: N/A
UN Markings: N/A
Packaging Group: N/A
S.G.: N/A
Internal Test Pressure: N/A

## PRODUCT DIMENSIONS:

Dimensions: 195 (L) x 145 (W) x 315 (H) mm Mass of Empty Package: 375q

Nominal Volume 0.008 m³ per unit

Bulk Equivalent: 2 kg (@ 250 kg/m³)