


## PRODUCT INFORMATION

**PRODUCT NAME:** Medium-Fibreboard-5L-Metal-Inner    **PRODUCT TYPE:** UN Approved DG packaging  
**PRODUCT CODE:** GP-4G16-IP3-1x5L-45

**DESCRIPTION:** Dangerous Goods Approved Combination Package with fibreboard outer box, EPS inserts, liner bag & 1 x 5 L metal jerrican with push closure for the transport of Dangerous Goods. IATA Compliant

### PHOTOGRAPHS



Fill contents



Place closure concentric with opening



Force the closure snug into the opening



Use the diagram on the closure to open

### Packaging System

**FALCON TEST ENGINEERS REPORT No:** 1425A

### ASSEMBLY & CONFIGURATION OF PACKAGING:

Place the filled inner packaging into the box. Ensure that it is in a stable upright position. Place EPS inserts over the inner packaging. Seal plastic bag with a "goose-neck tie". (Twist slack of bag tightly, fold over so that it forms a neck, and secure with elastic bands). Tuck neck into box. Close and seal the box with 48 mm pressure sensitive self adhesive tape in the same manner that the base of the box has been sealed. Add the required amount of absorbent material if specified. Label the box as required.

(Make sure that the labels or any other markings are not obliterated or obscured in any way).

Note: The use of other packaging methods or components may render the approval of this package invalid.

### MARKINGS & APPROVAL:

**Approval No.:** 60083  
**UN Markings:** UN 4G/Y17.5/S/##/AUS/VB60083  
**Packaging Group:** II&III  
**S.G.:** 1.6  
**Internal Test Pressure:** 180 kPa