



A.B.N. 67 054 007 162  
HAZPAK PTY LTD 44 Stephen Rd, Dandenong South Vic. 3175 Australia  
Postal Address: P.O. Box 4000, Dandenong South Vic. 3164 Australia  
Tel: (03) 9706 8058 Fax: (03) 9706 7593 Intl. Tel: 61 3 9706 8058  
E-mail: hazpak@hazpak.com.au

## PRODUCT INFORMATION

**PRODUCT CODE:** GP-EQ8-IP2-1x1L-58

**PRODUCT TYPE:** UN Approved Dangerous Goods packaging

**DESCRIPTION:** 'Excepted Quantity Combination Pack' with fibreboard outer box, fibreboard stabilising inserts, liner bag, 1 L HDPE rectangular jar with 58 mm screw closure and annular gasket and orientation labels for transport of Dangerous Goods.

IATA Compliant.

### PHOTOGRAPHS



**Inner Package**



**Combination Package**

**FALCON TEST ENGINEERS REPORT No:** 3450

### ASSEMBLY & CONFIGURATION OF PACKAGING:

Fill the inner packaging with substance, place the closure and tightly close using the spanner. Place the inner packaging into the outer fibreboard box. Ensure that it is in a stable upright position and that it is seated firmly on the bottom 'X' insert. Place the top 'X' insert over the inner packaging. Seal plastic bag with a "goose-neck tie". Twist slack of bag tightly, fold over so that it forms a neck, and secure with elastic bands. Tuck neck into box. Close and seal the box with 48 mm pressure sensitive self adhesive tape in the same manner that the base of the box has been sealed. Add the required amount of absorbent material if specified. Label the box as required.

**(Make sure that the labels or any other markings are not obliterated or obscured in any way).**

**Note:** The use of other packaging methods or components may render the approval of this package invalid.

### MARKINGS & APPROVAL:

<b>Approval No.:</b>	N/A
<b>UN Markings:</b>	N/A
<b>Packaging Group:</b>	N/A
<b>S.G.:</b>	N/A
<b>Internal Test Pressure:</b>	N/A

### PRODUCT DIMENSIONS:

<b>Dimensions:</b>	195 (L) x 140 (W) x 300 (H) mm	<b>Mass of Empty Package:</b>	390g
<b>Nominal Volume</b>	0.008 m <sup>3</sup> per unit		
<b>Bulk Equivalent:</b>	2 kg (@ 250 kg/m <sup>3</sup> )		