



HAZPAK PTY LTD 44 Stephen Rd, Dandenong South Vic. 3175 Australia
Postal Address: P.O. Box 4000, Dandenong South Vic. 3164 Australia
Tel: (03) 9706 8058 Fax: (03) 9706 7593 Intl. Tel: 61 3 9706 8058
E-mail: hazpak@hazpak.com.au
A.B.N. 67 054 007 162

PRODUCT INFORMATION

PRODUCT CODE: STP-4G20-EPS27-IP2-1x1.1L-115 (DS-IS-TS-27-1C) **PRODUCT TYPE:** Infectious Substances and Biological Substances

DESCRIPTION: '602/650 Insulated Specimen Transport Pack' with fibreboard outer box, EPS insulating box, corflute stabilising insert, re-sealable plastic bag (Primary Receptacle), 1.1 L HDPE round jar with 115 mm screw closure and plug insert (Secondary Package) and 4 x absorbent pads for transport with chilling mediums or at ambient temperature. IATA COMPLIANT.

NOTE: If transporting UN 2814 or UN 2900 place the 6.2 Class label over the UN 3373 label, and mark proper shipping name over 'Biological Substance Category B' marking.
The absorbent material supplied absorb up to 200 mL of product. Additional absorbent pads can be purchased separately if required.

PHOTOGRAPHS



Primary Receptacle and Secondary



Combination Packaging System

FALCON TEST ENGINEERS REPORT No.: 3618

CONFIGURATION OF PACKAGING:

Four absorbent pads and re-sealable plastic bag are placed inside the 'Hazpak' 1.1 L HDPE jar. The jar is sealed by placing the plug insert into the 1.1 L HDPE jar and the lid screwed closed. The 1.1 L HDPE jar is inserted into the EPS insulating box and the corflute stabilising insert is placed on top of the jar and the EPS insulating box is closed. Close and seal the fibreboard box with 48 mm pressure sensitive self adhesive tape in the same manner that the base of the box has been sealed. Add the required amount of absorbent material if specified. Label the box as required.

If using dry ice, the box should be pierced in the position marked to allow for venting.

(Make sure that the labels or any other markings are not obliterated or obscured in any way).

Note: The use of other packaging methods or components may render the approval of this package invalid.

MARKINGS & APPROVAL:

Approval No.: 3509
UN Markings: UN 4G/CLASS 6.2/**/AUS/3509/HAZPAK
Packaging Group: N/A
S.G.: N/A
Internal Test Pressure: 180 kPa at Ambient and -95 kPa at +55°C & -40°C

PRODUCT DIMENSIONS:

Dimensions: 310 (L) x 220 (W) x 285 (H) mm **Bulk Equivalent:** 4.9 kg cubic (@ 250 kg/m³)
Nominal Volume: 0.02 m³ per unit **Mass of Empty Package:** 765 grams ??